

DRO PROS

4992 Allison Parkway Suite G Vacaville, CA 95688 (707) 452-8434 / 8437

WBL250F 10" x 22" Lathe

\$2,124 - \$2,624









10" x 30"

X & Z Power Feed 1

Reversible Leadscrew

Lever-Lock tailstock

WEISS WBL250F - Description

The WBL250F lathe is an incredible value. Cross and carriage both have power feed in both directions. Quick Change toolpost, DRO and threading dial optional. Cuts 53 different threads - more than any other lathe! For boring and threading operations, the leadscrew direction is easily reversible, by changing a knob on the front panel, NOT by changing gears inside the gearbox. Two oil reservoirs ensure a long life. The power feed engages the keyway or slot in the leadscrew, which means you don't wear out the leadscrew threads when you engage power feed. Our best value!

WEISS WBL250F - Specifications		
Motor	1.5 HP Brushless DC / 1,100 Watts	
Speed range	50 - 2,000 rpm	
Speed	Variable	
Power Transfer	Belt Drive	
Distance Between Centers	21.63"	
Swing over bed	9.84"	
Swing over cross slide	5.92"	
Cross slide travel	4.53"	
Carriage travel	23.5"	
Compound travel	2.78"	
Tailstock quill travel	2.98"	
Width of bed	5.26"	
Spindle bore	1.02"	
Spindle taper	MT4	
Tailstock taper	MT2	
Carriage Leadscrew Diameter / Pitch	3/4" - 8 TPI	
Cross Slide Leadscrew Pitch	10 TPI	
Compound Leadscrew Pitch	20 TPI	
Faceplate Diameter	9.5"	
Threading Ability	53 Total Threads	
Inch threads	8-9-9.5-10-11-12-13-14-15-16-18-19-20-22-23-24-26-	
	28-30-32-36-38-40-44-46-48-52-56-60-64-72-80	
Metric threads	.354045506070758090-1.0-1.2-1.25-1.4-	
Metric tiffeads	1.5-1.6-1.75-1.8-2.0-2.4-2.5-3.0	
Power Supply	110 Volts	
Hardened and Ground Bed	Yes	
Main Body Dimensions	18"W x 43.38"L	
With Handles Dimensions	23.25"W x 43.38"L	
Base Footprint	5.25"W x 36.75"L	
Shipping Dimensions	49"L x 23"W x 24"H	
Machine Weight	285 lbs	
Shipping Weight	357 lbs	



DRO PROS

4992 Allison Parkway Suite G Vacaville, CA 95688 (707) 452-8434 / 8437

WBL250F 10" x 22" Lathe

\$2,124 - \$2,624









10" x 30"

LED RPM Panel N

Hardened Bedway

WEISS WBL250F - Standard Features		
Motor	1.5 HP Maintenance Free Brushless DC	
T-Slots in cross slide	YES	
Noiseless, Vibration Free Belt Drive	YES	
Lever lock tool-less tailstock	YES	
Digital Speed Control	YES	
Apron and Gearbox Oil Reservoirs	YES	
Quick-Change Gearbox	YES	
Knob on front for reversing leadscrew	YES	
Hardened and Ground Bed	YES	
Power Carriage	YES - Both Directions	
Power Cross Feed	YES - Both Directions	
Leadscrews	All are "Inch" Imperial not Metric	
WEISS WBL250F - Included Accessories		

WEISS WBL250F - Included Accessories		
Toolbox	Single Gear Spacer Bushing	
5" (125mm) 3 Jaw Chuck	8/10mm Open Ended Wrench	
3 Piece Outside Chuck Jaw Set	12/14mm Open Ended Wrench	
3 Piece Inside Chuck Jaw Set	17/19mm Open Ended Wrench	
4 Way Tool Post	Flat Blade Screwdriver	
Chuck Guard	Phillips Screwdriver	
Splash Guard	Oiling Bottle w/ Nozzle	
Chip Tray	Extra Fuse	
Spare Double Gearset Bushing	6 Piece Allen Wrench Key Set	
Lathe Chuck Key	Spanner Wrench	
MT2 Dead Center	Toolpost Spanner Wrench	
MT4 Dead Center	11 Extra Threading Gears	
WEISS WEI 250F Ontional Accessories		

WEISS WBL250F - Optional Accessories		
Pre-installed magnetic Digital Readout (DRO)	\$400.00	
Quick Change Toolpost	\$155.00	
Steady Rest	\$32.99	
Follow Rest	\$32.99	
Faceplate	\$31.99	
4 Jaw Chuck	\$84.99	
Backing Plate	\$26.99	
Threading Dial	\$22.99	
Luxury Stand	\$359.00	